



عمق یاب پرتابل چاههای عمیق و نیمه عمیق

PLS 30-150

The PLS 30, 50, 75, 100 and 150 are high tech designed handheld units, with 30 to 150 meters of cable and a **built-in brake**.

Technical specifications:

Measuring tape:

30 to 150 meters of polyethylene coated twin-leader steelwire with printed metric numbers in metres and centimetres.
Dimension 9 x 2 mm.

Probe standard version:

Stainless steel AISI 303. Dimension \varnothing 12 mm x 200 mm.
Weight aprox. 115 grams.

Probe special version:

Stainless steel AISI 303. Dimension \varnothing 10 mm x 200 mm.
Weight aprox. 90 grams.

Electronic circuit:

Integrated and waterproof with built-in electronic switch and low energy consumption.

Indication:

Sound: Frequency aprox. 3000 Hz, 80 dB.
Light: \varnothing 8mm LED-diode, ultrabright

Cablereel:

Shockproof plastic material (ABS).

Frame:

Steel frame with **built-in brake**.

Battery:

9 volt alkaline, type 6LR61 or similar.
Dimensions 17 x 26 x 47 mm

Meter dimensions:

Height 340 mm, Width 240 mm, Depth 190 mm.

Weight:

PLS 30: 1,8 kg.
PLS 50: 2,1 kg.
PLS 75: 2,3 kg.
PLS 100: 2,9 kg.
PLS 150: 3,6 kg.

Shipvolume:








18 litre

Unit 7, 3rd floor , No. 17 , 3rd Street
Dorahi Asad Abadi, Valiasr Ave.
Tehran Postcode :14336-33647, IRAN
Telfax: +98(0)21-8855 7352 - 54

تهران خیابان ولیعصر بالاتر از دوراهی اسدآبادی (یوسف آباد)
خیابان سوم پلاک ۱۷ طبقه سوم واحد ۷
کدپستی: ۱۴۳۳۶-۳۳۶۴۷
تلفکس : ۰۲۱-۸۸۵۵۷۳۵۲-۵۴

Portable Water Meter

انواع عمق یاب های پرتابل

| | Measuring Depth max. [m] | Probe Stainless Steel | Measurements HxWxD [mm] | Weight [kg] | Model Light- and Soundindication |
|--|--|--|--|--------------------------|--|
|  | 15 | ø12x130 | Ø 188 x 75 | 0,7 | PLS 15 Mini |
|  | 15 30 50 | ø12x130 ø12x200 ø12x200 | 330x250x180 330x250x180 330x250x180 | 1,7 2,0 2,4 | PLS 15 Box PLS 30 Box PLS 50 Box |
|  | 30 50 75 100 | ø12x200 ø12x200 ø12x260 ø12x260 | 370x260x220 370x260x220 370x260x220 370x260x220 | 2,5 2,9 3,4 3,9 | PLS 30 PLS 50 PLS 75 PLS 100 |
|  | 150 200 300 | ø12x260 ø12x260 ø12x260 | 410x310x230 410x310x230 410x310x230 | 5,1 6,1 7,9 | PLS 150 PLS 200 PLS 300 |
| For Ballast tanks:  | | With especially designed probe and adjustable sensitivity... | | | |
| | 30 50 75 | ø20x135 ø20x135 ø20x135 | 370x260x220 370x260x220 370x260x220 | 2,6 3,0 3,5 | PLS 30 SW PLS 50 SW PLS 75 SW |
| | more lengths on request! | | | | |
|  | 300 400 500 | ø12x350 ø12x350 ø12x350 | 450x400x245 450x400x245 450x400x245 | 10,2 12,1 15,1 | PLA 300 PLA 400 PLA 50 |
| | more lengths on request! | | | | |
|  | Accessories/Spare parts: Probe diameter 10 mm Switch for sound indication, all models Adjustable sensitivity, all models Adapter with carabinhook for watersampler Battery 9 Volt Alkaline Probe (weight) Ø 12 x 100mm Probe (weight) Ø 12 x 160mm | | | | |

Water Level Meters are made in lengths from 15 to 1000 metres.

Unit 7, 3rd floor , No. 17 , 3rd Street
Dorahi Asad Abadi, Valiasr Ave.
Tehran Postcode : 14336-33647, IRAN
Telfax: +98(0)21-8855 7352 - 54

تهران خیابان ولیعصر بالاتر از دوراهی اسدآبادی (یوسف آباد)
خیابان سوم بلاک ۱۷ طبقه سوم واحد ۷
کدپستی: ۱۴۳۳۶-۳۳۶۴۷
تلفکس: ۰۲۱-۸۸۵۵۷۳۵۲-۵۴